

# HV-G/HW-G Series

*Platform Scales*



**Reliable and Rugged!**  
**Outstanding Price Performance**



**A&D**  
A&D MERCURY PTY. LTD.

*...Clearly a Better Value*

# "Value" you can trust

## Platform Scales

### Two Types of Displays

#### Large and Clear Display

Digit height : LCD 25mm/VFD 20mm



**LCD**

Portable Battery Operation  
Operate in areas  
with low or no power.

**VFD**

Easy to see even in dark areas



#### Printer (Option only for VFD Type)

Dot Impact Printer  
Print out your data for  
safe keeping.



### Water and Dust Resistant

The stainless steel weighing pan and sealed base are resistant to water and dust. (IP-65)  
The weighing pan is easy to clean.

No Corner Pieces

Clean

Safe

Stainless Steel Weighing Pan



#### Water and Dust Resistant Protection for Load Cell Sensor

The Gore-tex® membrane wicks moisture away and keeps it away.

Gore-Tex® is a registered trade mark of W. L. Gore & Associates.



Popular Standard Medium Type

Large Floor Scale

**HV-G series**

#### Triple Range

Resolution can be changed automatically for 3 capacity levels

#### More Sophisticated Functions

##### ● Comparator

Set the high and low weight targets and show HI/OK/LO on the display.

##### ● Comparator Buzzer with OP-03

Optional comparator output sounds buzzer selected comparator settings.

##### ● Setpoint Control for Simple Batching

The weighing data can be controlled at 3 setpoints, Full Flow/Preliminary/Zero Band outputs.

# HV-G/HW-G Series

Wide Selection  
14 Models  
3 Platform  
Sizes

Compact  
Bench Scale Type



Type



HW-G Series

1/10,000 High Resolution

Ideal for applications  
requiring enhanced resolution.

ations

● **Tilting Meter Head**

Meter head tilts on the column to adjust for the best viewing angle. Relieves neck and eye strain.

● **Standard RS-232C**

Bi-directional RS-232C to connect with PC and AD-8121 printer.

● **Counting and % Function**

● **M+ Function for totaling weighing data**

Wide Variety of Applications



Food Processing/Fish Industry

Food Packaging

Industrial/Parts Counting



Pharmaceutical/Paint Mixing

Shipping



## Model Selection Guide

Which model is best for you ?

Model

HV-□□□ KGL...LCD  
Capacity V...VFD

HW-□□□ KGL...LCD  
Capacity V...VFD

Display : LCD (L Type) or VFD (V Type)  
Capacity : HV-15, 60, 200(kg) / HW-10, 60, 100, 200(kg)  
Resolution : 0.001kg to 0.1kg/0.002 lb to 0.2 lb  
Pan Size : Large (390 × 530 mm/15.4 × 20.9 inches)  
Medium (330 × 424 mm/13.0 × 16.7 inches)  
Small (250 × 250 mm/9.8 × 9.8 inches)  
Range : Single Range (HW-G Series)  
0.001kg to 0.02kg/0.002 lb to 0.05 lb  
Triple Range (HV-G Series)  
Example: HV-15KGL

Capacity : 3kg/6 lb Resolution : 0.001kg/0.002 lb  
Capacity : 6kg/15 lb Resolution : 0.002kg/0.005 lb  
Capacity : 15kg/30 lb Resolution : 0.005kg/0.01 lb

## Specifications

### HV-GL/GV Series

Display Type	Liquid Crystal Display									Vacuum Fluorescent Display									
Model	HV-15KGL			HV-60KGL			HV-200KGL			HV-15KGV			HV-60KGV			HV-200KGV			
Capacity(kg)	15	6	3	60	30	15	220	150	60	15	6	3	60	30	15	220	150	60	
Resolution(kg)	0.005	0.002	0.001	0.02	0.01	0.005	0.1	0.05	0.02	0.005	0.002	0.001	0.02	0.01	0.005	0.1	0.05	0.02	
Capacity(lb)	30	15	6	150	60	30	500	300	150	30	15	6	150	60	30	500	300	150	
Resolution(lb)	0.01	0.005	0.002	0.05	0.02	0.01	0.2	0.1	0.05	0.01	0.005	0.002	0.05	0.02	0.01	0.2	0.1	0.05	
Max Count (Pieces)	15000			12000			11000			15000			12000			11000			
Operating Temperature	-10°C to 40°C																		
Linearity(g)	±5	±2	±1	±20	±10	±5	±100	±50	±20	±5	±2	±1	±20	±10	±5	±100	±50	±20	
Span Drift	20ppm/°C typ.																		
Pan Size	mm *	250 × 250			330 × 424			390 × 530			250 × 250			330 × 424			390 × 530		
	inches *	9.8 × 9.8			13.0 × 16.7			15.4 × 20.9			9.8 × 9.8			13.0 × 16.7			15.4 × 20.9		
Physical Dimensions	mm **	275 × 474 × 368			330 × 621 × 771			390 × 712 × 773			275 × 474 × 368			330 × 621 × 771			390 × 712 × 773		
	inches **	10.8 × 18.7 × 14.5			13.0 × 24.4 × 30.4			15.4 × 28.0 × 30.4			10.8 × 18.7 × 14.5			13.0 × 24.4 × 30.4			15.4 × 28.0 × 30.4		
Power	AC Adapter or 6 × D alkaline Batteries (600 hours)									AC									
Weight (approximately)	6kg/13.2 lb			11kg/24.3 lb			17kg/37.5 lb			7kg/15.4 lb			12kg/26.5 lb			18kg/39.7 lb			
Standard Accessories	AC Adapter, Display Cover, Manual									Display Cover, Manual									

### HW-GL/GV Series

Display Type	Liquid Crystal Display				Vacuum Fluorescent Display								
Model	HW-10KGL	HW-60KGL	HW-100KGL	HW-200KGL	HW-10KGV	HW-60KGV	HW-100KGV	HW-200KGV					
Capacity(kg)	10	60	100	220	10	60	100	220					
Resolution(kg)	0.001	0.005	0.01	0.02	0.001	0.005	0.01	0.02					
Capacity(lb)	20	150	200	500	20	150	200	500					
Resolution(lb)	0.002	0.01	0.02	0.05	0.002	0.01	0.02	0.05					
Max Count (Pieces)	10000	12000	10000	11000	10000	12000	10000	11000					
Operating Temperature	-10°C to 40°C												
Linearity(g)	±2	±10	±20	±40	±2	±10	±20	±40					
Span Drift	20ppm/°C typ.												
Pan Size	mm *	250 × 250		330 × 424		390 × 530		250 × 250		330 × 424		390 × 530	
	inches *	9.8 × 9.8		13.0 × 16.7		15.4 × 20.9		9.8 × 9.8		13.0 × 16.7		15.4 × 20.9	
Physical Dimensions	mm **	275 × 474 × 368		330 × 621 × 771		390 × 712 × 773		275 × 474 × 368		330 × 621 × 771		390 × 712 × 773	
	inches **	10.8 × 18.7 × 14.5		13.0 × 24.4 × 30.4		15.4 × 28.0 × 30.4		10.8 × 18.7 × 14.5		13.0 × 24.4 × 30.4		15.4 × 28.0 × 30.4	
Power	AC Adapter or 6 × D alkaline Batteries (600 hours)				AC								
Weight (approximately)	6kg/13.2 lb		11kg/24.3 lb		17kg/37.5 lb		7kg/15.4 lb		12kg/26.5 lb		18kg/39.7 lb		
Standard Accessories	AC Adapter, Display Cover, Manual				Display Cover, Manual								

\* Stainless Steel Weighing Pan (No Corner Piece) W × D \*\* W × D × H

Specifications are subject to change for improvement without notice.

### Options

OP-03 — RS-232C with Comparator Relay Out/Buzzer  
OP-04 — RS-422/485 with Comparator Relay Out  
OP-06 — Built-In Printer for HV-GV and HW-GV

### Accessories

AX-PP156-S — Printer Paper for the OP-06 (10 rolls)  
AX-ERC-05-S — Ink Ribbons for the OP-06 (5 pieces)

**AND**  
A&D MERCURY PTY. LTD.

Your Dealer