Rinstrum Indicator Comparison

	Model	Ingress Protection	# 350 Ohm load cells	Function inputs	Set Points	Inputs/Outputs	RS232 Ports	RS485 Ports	Clock Calendar	Networking	Custom Printing	Software	Analog Output	Unit Switching	Dual Range %	Products/Recipes	Check Weigh Bands	Hold & Peak Hold	Counting	Report Printing	Totalising Printing	Logic Setpoints	Batching (stages)	Materials	Speeds for Fill	Modbus ASCII	Modbus TCP	EthernetIP	Data Storage	Tilt Compensation	Ethernet	LUA Scripting	Truck Weighing	Sum Master/Slave	BlueTooth Serial	Approvals	
	C520																																			
	C527	IP65	16	8	8	8	S A	S A	S A	S	S*	K501	A	S	S	1	-	S	-	S	S	-	-	-	-	S	S	A	S	-	S	A	S	-	A	1,2,5	
	R420	IP65	16	8	16	A 32 I/O	S A	S# A	A	S	S**	K401	A	S	S	1	-	S	S	S	S	S	-	-	-	-	-	-	A	-	A	A	-	-	A	1,2,3,5	General
													K402	A	S	S	250	-	S	S	S	S	S	-	-	-	-	-	-	A	-	A	A	-	-	A		MultiProduct
													K404	-	S	S	250	-	-	-	S	S	S	-	-	-	-	-	-	A	-	A	-	S	-	A		Truck
													K405	-	S	S	250	-	-	-	S	S	S	-	-	-	-	-	-	A	-	A	-	S	-	A		Static Axle
	R423	IP66											K410	A	-	S	100	-	-	-	S	S	S	10	1	3	-	-	-	A	-	A	A	-	-	A		Fill
													K411	A	-	S	100	-	-	-	S	S	S	10	6	3	-	-	-	A	-	A	-	-	-	A		Batch
													K412	A	-	S	100	-	-	-	S	S	S	10	20	3	-	-	-	A	-	A	-	-	-	A		Batch
	R427												K422	-	S	S	250	-	S	-	S	S	S	-	-	-	-	-	-	A	-	A	A	S	-	A	-	Dynamic Axle
													K491	A	S	S	250	-	S	S	S	S	S	-	-	-	-	-	-	A	S	A	A	-	-	A	2	Tilt
			-										K481	A	-	-	250	-	-	-	S	S	S	-	-	-	-	-	-	A	-	A	-	-	S	A	4	Summing
	R320/ R323	IP65	4~	-	-	-	-	-	-		-	-	K342							-	-	-													-		Basic
					1 in	S	A^	S			-	-	K344							-	-	-													A		+RS232 Comms
				1								-	K346	-	S	-	-	-	Manual	-	-	-	-	-											A	1,2,3,5	+IO
					1 in 2 out								K354																							A		+Clock+Custom Print
											S	S*	K356			S			S	S	S	S														A		+SetPoint
	X320	IP69K IP68	4~	1	-	3 Out 1 In	S	A^	S	S	S*	K376	-	S	S	1	3	S	S	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	A	1,2,3,5	Single
													K378				5		-	-																	Check weighing
	5000	IP65	8	4	4	4or2 Out 4or1 In	2	S	S	S	S*		A	-	S	1	-	S	-	-	S	-	-	-	-	S	-	-	-	-	-	-	-	-	A	1,2,3	General
	5100		8	6	6										S	99	-	S	S	S	S	-	S	20	3	S	-	-	-	-	-	-	-	-	A		Batch
	5200		12	4	4	4 Out 4 In									S	99	5	S	S	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A		Totalising Checkweigh
	5230		12	4	4										S	200	-	-	-	S	-	-	S	1	3	-	-	-	-	-	-	-	-	S	-	A		Truck
	6700		-	4	4	4 Out 4 In									S	-	-	-	-	-	S	-	-	-	-	-	-	-	-	-	-	-	-	S	A	4	Summer/Remote (Rinstrum,Avery,Gedge,A&D,Toledo,Barlo,Lodec,Phillips 1577, 1627)
	1203	IP65	6	1	2	2 Out 1 In	S	S	S	-	-		S	-	-	-	-	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A	-	Weight Transmitter

^	Convert RS232 port to RS485 with a 0080
#	Transmit only
~	8x350ohm for non trade
%	R400 Series Indicators are dual range & dual interval

*	Custom printing
**	Advance custom printing

S	Standard
A	Accessory or Option

Approvals		
	1	NMI Australia
	2	OIML R76
	3	New Zealand
	4	NMI S1/0/B
	5	NTEP (III/III L)